Shuttle

PRELIMINARY SPECIFICATIONS

XH610G

SLIM PC







PROCESSOR	Supports Intel® 12th/13th/14th Core® i3/i5/i7/i9 series, Pentium, and Celeron® LGA 1700 65W processors		
MEMORY	2 x SODIMM DDR5 5600 MHz, Supports dual channel up to 64GB (32GB x 2)		
VIDEO GRAPHICS	Intel UHD Graphics		
VIDEO OUTPUT	HDMI 2.0b x 2 + DisplayPort Supports triple independent displays		
AUDIO	Realtek ALC888S, HD audio		
ETHERNET	Intel Gigabit LAN x 1 (10/100/1000 Mb/s) Intel 2.5 GbE LAN x 1 (10/100/1000/2500 Mb/s)	Supports Wake on LAN function	
STORAGE INTERFACE	SATA 6 Gb/s		
ONBOARD CONNECTORS	Raiser card slot 4 pin fan connectors SATA connector		
FRONT PANEL	(1) Power Button(1) Power LED(1) HDD LED(2) USB 2.0	(2) USB 3.2 Gen 1 (1) MIC-in (1) Line-Out	
BACK PANEL	(2) HDMI (1) DisplayPort (2) USB 3.2 Gen 1 (2) USB 2.0	(1) DC-in (2) RJ45 Gigabit LAN (2.5 GbE LAN x 1, Gigabit LAN x 1) (2) Antenna holes	
DRIVE BAYS	(1) 2.5" HDD/SSD bay		
DIMENSIONS	9.8 (L) x 7.9 (W) x 3.1 (H) inches		
POWER	Input: 100 - 240V AC Output: 19.5V/9.23A DC	180W power supply	
ACCESSORIES	Quick Guide Screw package VESA bracket with screws Power adapter Power cord	Driver DVD PS01 (optional vertical stand) WLN-M (optional WLAN & Bluetooth kit)	
EXPANSION SLOT	 M.2 2280 M key slot (NVMe + SATA) M.2 2280 M key slot (SATA only) M.2 2230 E key socket (PCIe Gen 3x1, USB 2.0 PCI-E X16 	, CNVi)	
OPERATING TEMPERATURE	0°C to 50°C		
OS SUPPORT	Windows 11 64 bit, Linux (64 bit)		
CERTIFICATION	Safety: CB, BSMI, cTUVus	EMI: FCC, CE, BSMI, RCM, VCCI, UKCA	

For more information on all products, please contact us at sales@us.shuttle.com or 626.820.9000

© 2024 Shuttle Computer Group, Inc. All rights reserved. Specifications are subject to change without notice. Not responsible for any photographic or typographic errors. Photos shown may vary from actual look. Intel, the Intel logo, and Intel Core are trademarks of Intel Corporation or its subsidiaries in the US and/or other countries. ©Intel Corporation

Shuttle

CONNECTORS

XH610G


SLIM PC

Front View



- **1** USB 2.0 ports x 2
- 2 USB 3.2 Gen 1 x 2
- **3** Microphone input
- 4 Headphone output
- 5 Power on button with LED
- 6 LED indicator for hard disk drive

Back View



- **A** WLAN antenna hole x 2
- **B** Perforation for optional COM port
- **C** Kensington Lock
- **D** HDMI 2.0b port (video/audio) x 2
- E DisplayPort
- F 2.5 GbE LAN port
- G Gigabit LAN port

- H USB 3.2 Gen 1 port x 2
- I PCI-E X16 expansion slot
- J USB 2.0 ports x 2
- K DC-in
- L 4-pin connector for external power button, Clear CMOS & Power Button

For more information on all products, please contact us at sales@us.shuttle.com or 626.820.9000

© 2024 Shuttle Computer Group, Inc. All rights reserved. Specifications are subject to change without notice. Not responsible for any photographic or typographic errors. Photos shown may vary from actual look. Intel, the Intel logo, and Intel Core are trademarks of Intel Corporation or its subsidiaries in the US and/or other countries. ©Intel Corporation

Shuttle

XH610G

FEATURES

SLIM PC

intel.	intel.	intel.
CORE	CORE	CORE
i7	iS	i5

SUPPORTS INTEL® 12TH/13TH/14TH GENERATION PROCESSORS

Equipped with a LGA1700 socket, the XH610G supports Intel[®] Celeron[®], Pentium[®] and Core[™] i3/i5/i7/i9 65W processors. Integrated Ultra HD graphics and supports up to 64GB (32GB x 2) of DDR5-5600 memory.



PCI-E X16 SLOT

Expansion options like various add-on cards such as a video capture card or discrete graphic cards enables users to build a system for versatile 2D/3D media applications, suitable for multi-screen splicing for TV walls and other image processing applications.

*Maximum size supported for cards is 208.5 x 120 x 30 mm



TRIPLE DISPLAY

SUPPORTS TRIPLE DISPLAY

Connectivity to three independent displays are supported, suitable for delivering highquality 2D and 3D video showcases. Additionally, triple-screen splicing is supported for TV walls via the Intel[®] Graphics Command Center.



M.2

M.2 EXPANSION SLOTS

The XH610G is equipped with two M.2 slots (M.2 2280 Type M) to expand the storage or device. One M.2 2230 Type E slot is for installing Wi-Fi or Bluetooth modules for higher transmission bandwidth.



24/7 CERTIFIED

Approved for 24/7 operation, the XH610G uses industrial capacitors in order to meet the environmental operation demands of commercial applications.*

*For high ambient temperatures over 40°C, SSDs are recommended

For more information on all products, please contact us at sales@us.shuttle.com or 626.820.9000

© 2024 Shuttle Computer Group, Inc. All rights reserved. Specifications are subject to change without notice. Not responsible for any photographic or typographic errors. Photos shown may vary from actual look. Intel, the Intel logo, and Intel Core are trademarks of Intel Corporation or its subsidiaries in the US and/or other countries. ©Intel Corporation