

K15RK01

KIOSK



PROCESSOR	Rockchip RK3368 Octa Core 1.5GHz (ARM Cortex-A53)	
OPERATING SYSTEM	Android 8.1 Supports screen rotation	Supports HDMI output scaler functions (zoom in/zoom out)
MEMORY	DDR3L 2GB	
DISPLAY	15.6" 1920x1080 Full HD, LCD Backlight lifetime: 30,000 hours	True-Flat PCAP Multi-Touch, IP65 rating Brightness: 250 cd/m2
AUDIO	Internal speaker 2W x 2	
NETWORK	LAN x 1 (RGMII interface) 10/100/1000 MB/s Supports PoE (PD), 802.3at UART, Bluetooth 4.0	802.11 b/g/n, SDIO interface, 1T1R External antenna x 2 Miracast (wireless display support)
STORAGE INTERFACE	2.5" HDD x 1 (max 7 mm size) SD card x 1	16GB eMMC onboard
IC CARD READER	Friction Type User Card PC/SC 1.0 Standard Approval	CPU card and memory card compliant
NFC/RFID READER	ASK Manchester coding or Mifare: ISO14443A standard EM compatible 64 bits	
SD CARD READER	Supports FAT and NTFS	
CAMERA	2MP FHD	
OTHER PERIPHERALS	1D/2D barcode scanner	3" thermal printer w/auto cutter, 200mm/sec
PORTS	(8) USB 2.0 (for USB peripherals) (1) RJ45	(1) USB 2.0 (OTG)
VIEWING ANGLE (H/V°)	89 (left), 89 (right), 89 (up), 89 (down)	
MOUNTING	Counter, Pole, Wall	
OPERATING TEMPERATURE	0 - 35°C	
STORAGE TEMPERATURE	-20°C - 60°C	
RELATIVE HUMIDITY	20% - 80% RH (non-condensing)	
DIMENSIONS	14.6(L) x 12.2(W) x 19.7(H) inches	
POWER	65W 19V/3.42A (AC-adaptor to system) Supports auto power on after power fail	60W 24V/2.5A (AC-adaptor to printer) Supports EUP function when on standby (under 0.5W)
CERTIFICATION	BSMI, CB, CCC, CE, ETL, FCC Class A, LVD, RCM, R&TTE, VCCI	
OTHER CERTIFICATION	RoHS Compliance, Eup Lot6 Compliance (standby under 0.5W), Google Play (only CTS)	

For more information on all products, please contact us at sales@us.shuttle.com or **626.820.9000**